Product Information

AVENO Extra 15W-40

0002-000010



Description

AVENO Extra 15W-40 is a semi-synthetic high-performance, smooth-running engine oil for carburettor and diesel car engines with or without turbocharging and direct injection. Extended oil change intervals as per manufacturer's instructions. AVENO Extra 15W-40 is characterized by its excellent cold starting properties, minimization of fuel consumption, friction and wear. With AVENO Extra 15W-40, a reliable and heavy-duty engine oil has been developed.

Instructions for use

AVENO Extra 15W-40 is an engine oil for year-round use, and is ideal for all modern petrol and diesel car engines. AVENO Extra 15W-40 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification	
Specification	
• API SL/CF	• ACEA A3/B4
Recommendation	
• Fiat 9.55535-D2/-G2 • MB 229.1	• VW 501 01/VW 505 00

Properties

- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Suitable for catalytic converters

- Excellent cold starting properties, even at low temperatures
- A very stable and excellent viscosity behavior and shear stability
- Extensive protection against wear, corrosion and foaming
- Extended oil change intervals protect natural resources

Technical specifications			
Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	9.5	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	13.7	mm²/s	DIN 51659-2:2017-02
Viscosity Index	144		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Viscosity CCS at -20°C	4300	MPAS	ASTM D 5293:2020
Density at 15°C	868	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-39	°C	ASTM D 7346:2015
Total Base Number (TBN)	8.6	mgKOH/g	ASTM D 2896:2015