

Product Information

AVENO FS WIV-Combi 5W-30

0002-000035



Description

AVENO FS WIV-Combi 5W-30 is a synthetic smooth-running engine oil for modern petrol and diesel car engines with or without turbocharging and direct-injection. AVENO FS WIV-Combi 5W-30 is characterized by its minimization of fuel consumption, an excellent oil supply during cold starting and ensures a high level of wear and corrosion prevention. Extended oil change intervals as per manufacturer's instructions.

Instructions for use

AVENO FS WIV-Combi 5W-30 is an energy-efficient engine oil for year-round use and ideal for all modern petrol and diesel car engines. AVENO FS WIV-Combi 5W-30 extends the services life of the diesel particulate filter. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- API SN
- ACEA C3

Recommendation

- BMW Longlife-04
- Porsche C30
- Fiat 9.55535-S3
- VW 504 00/507 00
- MB 229.31, MB 229.51

Properties

- Excellent cold starting properties
- High shear stability
- Neutrality towards sealants
- Suitable for catalytic converters
- A very stable and excellent viscosity behavior, even at high speeds
- Fuel savings under all operating conditions
- Low evaporation, thus low oil consumption
- Extended oil change intervals protect natural resources

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	73.2	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	12.2	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	164		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Viscosity CCS at -30°C	5700	mPa*s	ASTM D 5293:2020
Density at 15°C	849	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-39	°C	ASTM D 7346:2015
Total Base Number (TBN)	6.6	mgKOH/g	ASTM D 2896:2015