# **Product Information**

# **AVENO MotorCycle 4 Stroke 10W-60**

0002-000136



#### Description

AVENO MotorCycle 4 Stroke 10W-60 is a heavy-duty engine oil for demanding 4-stroke motorbikes. It allows for fuel-saving engine operation and is specifically designed for wet and lubricated couplings. AVENO MotorCycle 4 Stroke 10W-60 is characterized by its excellent cold starting properties, as it ensures optimum lubrication reliability during the cold-running phase.

#### Instructions for use

AVENO MotorCycle 4 Stroke 10W-60 is especially suitable as a high-performance, smooth-running engine oil for all motorcycles, when the specification SAE 10W-60 is required. AVENO MotorCycle 4 Stroke 10W-60 meets the high-tech demands of the latest high-performance engine generation. For professional racing we recommend our racing products.

## **Quality classification**

### **Specification**

• API SL • JASO MA/MA2

#### **Properties**

- Excellent cold starting properties
- Very good detergent and dispersing properties
- Low evaporation, thus low oil consumption
- Prevention of silting, varnish, coking and corrosion
- Very stable viscosity index
- Fast lubrication of the engine
- Prevention of oil-dependent deposits in combustion chambers, in the piston ring area or on valves

Technical specifications			
Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	160.1	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	23.1	mm²/s	DIN 51659-2:2017-02
Viscosity Index	174		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Viscosity CCS at -25°C	5900	mPa*s	ASTM D 5293:2020
Density at 15°C	855	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-39	°C	ASTM D 7346:2015
Total Base Number (TBN)	10.3	mgKOH/g	ASTM D 2896:2015