

# Product Information

## AVENO Dexron III G RED

0002-000158



### Description

AVENO Dexron III G RED is designed on a basis of hydrocrack oils and PAO with special additives and inhibition. AVENO Dexron III G RED was developed especially for the indicated specifications and purposes. It provides maximum lubrication and wear protection thanks to its special additives. AVENO Dexron III G RED is a universal ATF (Automatic Transmission Fluid) of the latest generation for all automatic gearboxes with and without regulated converter lockup clutch (so-called gear-clutch lock-up), for which gear fluids of type Dexron III H are required.

### Instructions for use

AVENO Dexron III G RED is especially suitable for use in gearboxes with ATF Dexron III G specifications. AVENO Dexron III G RED is miscible with all brands of ATFs. It is recommended to flush with AVENO Dexron III G RED first, before the final filling with AVENO Dexron III G RED is performed. The operating instructions of the automobile and engine manufacturer must be observed.

### Quality classification

#### Specification

- GM Dexron® III G
- Ford MERCON®

#### Recommendation

- DTFR 13C100 (236.1), MB 236.5
- VOITH H55.6335.XX (G607)
- Ford WSA-M2C195-A
- ZF TE-ML 02F/03D/04D/09/11B/14A/17C
- MAN 339 Typ Z-1/V-1

### Properties

- Reliable protection against wear, corrosion and foaming
- Problem-free at very low temperatures
- Very good oxidation stability
- Neutral towards sealing agents
- High and very stable viscosity index
- Very low pour point
- Well coordinated friction properties
- Neutral behavior towards non-ferrous metals due to inhibition

### Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	35,0	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	7,2	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Viscosity Index	176		DIN ISO 2909:2004-08
Appearance	RED		VISUELL
Density at 15°C	848	kg/m <sup>3</sup>	DIN EN ISO 12185:1997-11
Pour Point	-54	°C	ASTM D 7346:2015