Product Information

AVENO Mineral SAE 80 GL-4

0002-000199



Description

AVENO Mineral SAE 80 GL-4 is an oil for manual gearboxes designed on the basis of mineral oils and special additives. At high temperatures, an optimal gear lubrication is ensured. AVENO Mineral SAE 80 GL-4 reduces friction and prevents wear and corrosion. Even under extreme dynamic conditions, a stable oil film is guaranteed for the lubrication.

Instructions for use

AVENO Mineral SAE 80 GL-4 guarantees proper lubrication, even in hypoid-geared gearboxes. The operating instructions of the automobile and gearbox manufacturer must be observed.

Quality classification					
Specification					
• API GL-4					
Properties					
• Less wear		 Very good oxidation st 	Very good oxidation stability		
Resistant oil film		 Neutral towards metal 	 Neutral towards metal and sealing agents 		
Technical specifications					
Properties	Data	Unit	Testing under		

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	80.5	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	9.9	mm²/s	DIN 51659-2:2017-02
Viscosity Index	103		DIN ISO 2909:2004-08
Appearance	YELLOW		VISUELL
Density at 15°C	875	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-33	°C	ASTM D 7346:2015

Deutsche Ölwerke Lubmin GmbH | Freesendorfer Weg 4 | 17509 Lubmin | Phone +49 38354 / 179530 | Fax +49 38354 / 179579

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments of the Deutsche Ölwerke Lubmin GmbH. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.