Product Information

AVENO Gear Super Synth. 75W-80 GL-4

0002-000204



Description

AVENO Gear Super Synth. 75W-80 GL-4 is a semi-synthetic gear oil especially for maximum-duty hypoid toothed gearboxes. AVENO Gear Super Synth. 75W-80 GL-4 is designed on a basis of high-quality solvent refined and synthetic base oils and specially coordinated additives with high-pressure (EP) active agents and other supplements. This ensures compliance with today's practical requirements is exceeded.

Instructions for use

AVENO Gear Super Synth. 75W-80 GL-4 is a high-performance gear oil for use in maximum-duty hypoid toothed gearboxes (axle drives, manual gearboxes, etc.), where high-pressure gear oils are required.

Quality classification

Specification

• API GL-4

Recommendation

• PSA B71 2315

Properties

- A very good oxidation resistance
- A low pour point
- A high viscosity index

- Most extensive protection against rust formation, corrosion, foaming
- Excellent high-pressure (EP) properties
- Fuel savings

Technical specifications			
Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	43.3	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	8.5	mm²/s	DIN 51659-2:2017-02
Viscosity Index	177		DIN ISO 2909:2004-08
Appearance	LIGHT YELLOW		VISUELL
Density at 15°C	847	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-39	°C	ASTM D 7346:2015