# **Product Information**

## **AVENO Gear Extra Full Synth. LS 75W-140 GL-5**

0002-000222



### Description

AVENO Gear Extra Full Synth. LS 75W-140 GL-5 is a synthetic multi-purpose oil for highly stressed manual gearboxes. AVENO Gear Extra Full Synth LS 75W-140 GL 5 was developed based on the high quality fully synthetic base oils (PAO and Ester) with a special additive treatment and inhibition for limited slip applications. AVENO Gear Extra Full Synth. LS 75W-140 GL-5 is coordinated to the increased loads of manual gearbox oils, in order to ensure the gearbox functions flawlessly.

### Instructions for use

AVENO Gear Extra Full Synth. LS 75W-140 GL-5 guarantees proper lubrication, even in self-locking, hypoid-geared gearboxes. The operating instructions of the automobile and gearbox manufacturer must be observed.

# Quality classification Specification • API GL-4 • API GL-5 • MIL-L-2105 C • MIL-L-2105 D Recommendation • BMW 83 22 2 282 583, BMW 83 22 1 470 080 • Ford M2C187-A, Ford M2C192-A • BMW MSP/A • Ford M2C192-A + M2C118-A • Castrol SAF-XJ • GM 12346140, GM 1942386

### **Properties**

- Less wear
- · Very good oxidation stability
- Resistant oil film

- Excellent viscosity-temperature characteristics
- Neutral towards metal and sealing agents

Technical specifications			
Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	205.2	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	28.2	mm²/s	DIN 51659-2:2017-02
Viscosity Index	177		DIN ISO 2909:2004-08
Appearance	YELLOW		VISUELL
Density at 15°C	845	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-51	°C	ASTM D 7346:2015