

Product Information

AVENO Zentral Hydraulik Fluid GREEN

0002-000257



Description

AVENO Zentral Hydraulik Fluid is a special hydraulic oil on the basis of synthetic oils with high-quality additives. Thanks to its special formulation, the properties of AVENO Zentral Hydraulik Fluid play a crucial role. We guarantee an excellent cold stability. AVENO Zentral Hydraulik Fluid has a high performance as a central hydraulic oil in power steering, rear axle for hydrostatic drive of ventilators, alternators and air conditioning systems, for stability and traction systems (ABS/ASR/ASC), central locking, electro-hydraulic convertible top controls, hydraulic brake boosters and hydropneumatic suspension for VW, Audi, Seat and Skoda. Especially for use in cold countries.

Instructions for use

AVENO Zentral Hydraulik Fluid is designed for use from -60°C to +130°C and is therefore recommended for the latest developments on the automotive market.

Quality classification

Specification

- DIN 51524-2
- ISO 7308

Recommendation

- Land Rover Cold Climate PAS Fluid 14315
- Peugeot/Citroën 9979 A1
- MB 343.0
- SAAB 93 160 548
- Opel 1940 766
- VOLVO 30741424
- PSA B71 2710
- VW G 004 000

Properties

- Reliable protection against corrosion
- Extremely low pour point
- Improved viscosity and friction behavior
- A very good wear protection
- An excellent thermal stability
- A good foaming behavior
- Neutral towards sealing agents

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	25.3	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	7.1	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	267		DIN ISO 2909:2004-08
Appearance	GREEN FLOURESCENT		VISUELL
Density at 15°C	840	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-66	°C	ASTM D 7346:2015