# **Product Information**

**AVENO Circulating Oil CL 150** 

0002-000272



### Description

AVENO Circulating Oil CL 150 is produced on a basis of high-quality mineral oils and proven additives. Thanks to its special combination of active ingredients, it is suitable for use as a simple machine lubricant where no EP-additive oils are required.

#### Instructions for use

AVENO Circulating Oil CL 150 has very good properties as a lubricant. Therefore AVENO Circulating Oil CL 150 can preferably be used for industrial gears and circulation systems of low and medium loads, where lubricants are required in accordance with DIN 51517-2.

# **Quality classification**

## Specification

• DIN 51517-2 (CL)

## Properties

• A good wear protection

• A mild additive and is therefore particularly suitable for old machines

Prevents foam formation

• Inhibits rust and corrosion and protects against ferrous metal corrosion

• Good water separation characteristics

Technical specifications			
Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	150.0	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	14.8	mm²/s	DIN 51659-2:2017-02
Viscosity Index	98		DIN ISO 2909:2004-08
Appearance	YELLOW		VISUELL
Density at 15°C	885	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-18	٥°	ASTM D 7346:2015

Deutsche Ölwerke Lubmin GmbH | Freesendorfer Weg 4 | 17509 Lubmin | Phone +49 38354 / 179530 | Fax +49 38354 / 179579

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments of the Deutsche Ölwerke Lubmin GmbH. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.