## **Product Information**

## AVENO Ultra 20W-50

0002-000314



## Description

AVENO Ultra 20W-50 is an engine oil on mineral oil basis with selected additives for demanding petrol engines from 2001 and later, and 4-stroke motorbikes. AVENO Ultra 20W-50 has excellent lubricating film adhesion and good shear stability, as well as outstanding cleaning capability and high resistance to aging.

## Instructions for use

AVENO Ultra 20W-50 is intended for the typical operation of petrol engines in current and earlier (from 2001 onwards) cars, sport utility vehicles, vans and light trucks during maintenance measures recommended by vehicle manufacturers. Oils that meet the API SL requirements can be used wherever the API service category SJ and earlier categories are recommended. AVENO Ultra 20W-50 is also excellently suited as engine oil for motorbikes, when the specification SAE 20W-50 JASO MA/MA2 is required.

Quality classification			
Specification			
• API SL		• JASO MA-2	
Properties			
Technical specifications			
Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	19.1	mm²/s	DIN ISO 51562-2:1988-12
viscosity index	122		DIN ISO 2909:2004-08
appearance	YELLOW		VISUELL
density at 15°C	883	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-30	°C	ASTM D 7346:2015

Deutsche Ölwerke Lubmin GmbH | Freesendorfer Weg 4 | 17509 Lubmin | Phone +49 38354 / 179530 | Fax +49 38354 / 179579

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments of the Deutsche Ölwerke Lubmin GmbH. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.