

Product Information

AVENO MBike 15W-40

0002-000710



Description

AVENO MBike 15W-40 is a motor oil based on hydrocrack oils with selected additives for demanding 4-stroke motorcycles. It is characterized by high resilience and reliability and is specially designed for wet and oil-lubricated clutches. AVENO MBike 15W-40 has excellent lubricating film adhesion, good shearing stability, excellent cleaning properties and high aging resistance.

Instructions for use

AVENO MBike 15W-40 is suitable as motor oil for all motorcycles if the SAE 15W-40 specification is required.

Quality classification

Specification

- API SN
- JASO MA2

Properties

- Excellent cold start properties
- High oxidation stability
- Prevention of black sludge formation
- Outstanding shear stability
- Very good detergent and dispersing properties
- Very good viscosity-temperature behavior/catalyst suitability

Technical specifications

| Properties | Data | Unit | Testing under |
|------------------------------|-------------|--------------------|--------------------------|
| Kinematic Viscosity at 40°C | 107.1 | mm ² /s | DIN 51659-2:2017-02 |
| Kinematic Viscosity at 100°C | 14.3 | mm ² /s | DIN 51659-2:2017-02 |
| Viscosity Index | 136 | | DIN ISO 2909:2004-08 |
| Appearance | YELLOWBROWN | | VISUELL |
| Density at 15°C | 866 | kg/m ³ | DIN EN ISO 12185:1997-11 |
| Pour Point | -30 | °C | ASTM D 7346:2015 |
| Total Base Number (TBN) | 7.1 | mgKOH/g | ASTM D 2896:2021 |