Product Information

AVENO MBike 5W-30

0002-000807



Description

AVENO MBike 5W-30 is a motor oil based on hydrocrack oils with selected additives for demanding 4-stroke motorcycles. It is characterized by a very high oxidation stability, excellent lubricating film adhesion and reliability under any load and is specially designed for wet and oil-lubricated clutches. AVENO MBike 5W-30 protects the engine from deposits and ensures a long service life.

Instructions for use

Quality classification

AVENO MBike 5W-30 is suitable as motor oil for all air- and water-cooled 4-stroke motorcycles if a viscosity of 5W-30 is required. The operating instructions of the engine manufacturer must be observed!

Specification • API SN • JASO MA2

Properties

- Very good shear stability
- Very good cold start properties
- Prevention of premature wear
- Tried and tested additives

- High safety reserves even under boundary lubrication conditions
- Optimum function of engine, clutch and transmission
- Very good resistance to oxidation and high temperature engine deposits

| Technical specifications | | | |
|------------------------------|-------------|---------|--------------------------|
| Properties | Data | Unit | Testing under |
| Kinematic Viscosity at 40°C | 69.3 | mm²/s | DIN 51659-2:2017-02 |
| Kinematic Viscosity at 100°C | 11.6 | mm²/s | DIN 51659-2:2017-02 |
| Viscosity Index | 164 | | DIN ISO 2909:2004-08 |
| Appearance | YELLOWBROWN | | VISUELL |
| Density at 15°C | 851 | kg/m³ | DIN EN ISO 12185:1997-11 |
| Pour Point | -42 | °C | ASTM D 7346:2015 |
| Total Base Number (TBN) | 8.0 | mgKOH/g | ASTM D 2896:2021 |